



# Panel-Loc Plus™

## Product Guide

HELPFUL INFORMATION ON PANELS, TRIMS, GUTTERS AND ACCESSORIES



▲ This guide includes details for Panel-Loc.



***We promise to improve your business  
by accurately providing quality products  
right when you need them. Every time.***

Visit our website for more product information, testing, installation guides, energy ratings, warranties, photo gallery, roofing visualizer, and more.

**centralstatesco.com**

# INDEX

---

*Information in this catalog may vary by plant location.  
Please call your salesperson to verify product availability.*

Panel-Loc Plus	
Panel Codes, Fastener Spacing, Section Properties	4-5
Panel-Loc	
Panel Codes, Fastener Spacing, Section Properties	6-7
Care and Handling, Siphon Groove	8-9
Converting Pitch to Degree	10
Square Conversions	11
Gauge and Color Codes	12
Roof Trims	13-14
Wall Trims	14-15
Soffit/Fascia	16
Accessories	17-18

*NOTICE: The application and detail drawings in this manual are strictly for illustration purposes and may not be applicable to all building designs or product installations. Projects should conform to local building codes. Central States Manufacturing is not responsible for the performance of the material if it is not installed correctly.*

*Information contained in this booklet was in effect at the time of publication and is subject to change without notice.*

# WARRANTIES

---



Warranties are available in paper format and downloadable from our website. After the job is complete, fill out a warranty with your contractor/installer details and the Central States order number. Give the warranty to the building owner to keep for their records. Optional warranty registration is available online.

*Learn more at [centralstatesco.com/warranties](https://centralstatesco.com/warranties)*

# PANEL-LOC PLUS

Panel-Loc Plus is available in Ultra 26 gauge, Prime 29 gauge, and Standard 29 gauge; in painted or bare Galvalume®. Ultra and Prime panels feature CentralGuard® protection and a lifetime paint warranty. Standard panels feature a 40-year paint warranty.

CentralGuard is our specific combination of everything that goes into making the highest-quality metal panels. Choose CentralGuard for the perfect balance of fade protection, rust blocking, and dent resistance.

Bare (unpainted) Galvalume® and galvanized panels from Central States have an acrylic coating which eliminates using oils during manufacturing and eliminates fingerprinting and foot marking during installation.

The minimum roof slope for the 3/4" Panel-Loc Plus™ is 2 1/2:12. If slopes less than 3:12 are needed, International Building Code (IBC) allows a sealant tape to be used on the laps of the panel.

## PANEL CODES

PANEL PROFILE	TYPE	CODE
Panel-Loc Plus™	Ultra SMP	PP6(color)
Panel-Loc Plus™	Prime SMP/FEVE*	PP9(color)
Panel-Loc Plus™	Standard	PP9(color)ST
Panel-Loc Plus™	Thrifty SMP	PP6(color)TH

\*FEVE= Flourinated Polymer Paint System

# FASTENER SPACING

Follow the suggested fastener patterns below for interior or panel termination. Screws may be placed in either the flat or the rib. In the overlap condition, avoid using fasteners in the major rib as this may damage the siphon groove.

Fastener pattern at panel termination (Eave, endlap, valley, ridge, high eave)



Fastener pattern at interior of panel



# SECTION PROPERTIES - PANEL-LOC PLUS

## 36" WIDE, PANEL-LOC PLUS™ PANEL

Gauge	Thickness (inches)	Weight (psf)	Yield Stress (ksi)	Top in Compression (Positive Bending)			Bottom in Compression (Negative Bending)		
				I <sub>xx</sub>	S <sub>xx</sub>	Ma	I <sub>xx</sub>	S <sub>xx</sub>	Ma
				in <sup>4</sup> /ft	in <sup>3</sup> /ft	in.kips/ft	in <sup>4</sup> /ft	in <sup>3</sup> /ft	in.kips/ft
26 ULTRA	0.0185	0.866	80.0	0.0133	0.0220	0.7913	0.0093	0.0198	0.7123
29 PRIME	0.0150	0.704	80.0	0.0110	0.0181	0.6493	0.0073	0.0160	0.5760

Section properties and allowables are calculated in accordance with 1996 AISI Specifications and 1999 AISI Supplement No. 1. I +/- is for deflection determination. S +/- is for bending determination. Ma is allowable bending moment. All values are for one foot of panel width. These loads are for panel strength. Frames, purlins, fasteners and all supports must be designed to resist all loads imposed on the panel. Allowable outward loads based on stress have been increased by 33.33% for wind uplift. Allowable loads for deflection are based on deflection limitation of span/180 or span/240. For roof panels, self weight of the panel has to be deducted from the allowable inward load to arrive at the actual "live load" carrying capacity of the panel. Minimum bearing length must be checked. Minimum deliverable bare steel thickness should not be less than 0.95 of design thickness.

# THEORETICAL ALLOWABLE LIVE & WIND LOADS

## SINGLE SPAN CONDITION

Span (feet)	29 Gauge & 80 ksi				26 Gauge & 80 ksi			
	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)
2	108.2	108.2	90.1	127.7	131.9	131.9	109.3	157.9
2.5	69.3	61.5	46.2	81.7	84.4	74.6	55.9	101.1
3	48.1	35.6	26.7	56.7	58.6	43.2	32.4	70.2
3.5	35.3	22.4	16.8	41.7	43.1	27.2	20.4	51.6
4	27.1	15.0	11.3	31.9	33.0	18.2	13.7	39.5
4.5	21.4	10.6	7.9	25.2	26.1	12.8	9.6	31.2
5	17.3	7.7	5.8	20.4	21.1	9.3	7.0	25.3
6	12.0	4.5	3.3	14.2	14.7	5.4	4.0	17.5

## TWO SPAN CONDITION

Span (feet)	29 Gauge & 80 ksi				26 Gauge & 80 ksi			
	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)
2	96.0	96.0	96.0	121.0	118.7	118.7	118.7	175.4
2.5	61.4	61.4	60.1	77.5	76.0	76.0	72.8	112.3
3	42.7	42.7	34.8	53.8	52.8	52.8	42.2	78.0
3.5	31.3	29.2	21.9	39.5	38.8	35.4	26.5	57.3
4	24.0	19.6	14.7	30.3	29.7	23.7	17.8	43.9
4.5	19.0	13.7	10.3	23.9	23.5	16.7	12.5	34.6
5	15.4	10.0	7.5	19.4	19.0	12.1	9.1	28.1
6	10.7	5.8	4.3	13.4	13.2	7.0	5.3	19.5

## THREE OR MORE SPAN CONDITION

Span (feet)	29 Gauge & 80 ksi				26 Gauge & 80 ksi			
	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)
2	112.1	112.1	112.1	168.1	138.7	138.7	138.7	204.9
2.5	71.8	71.8	71.8	107.6	88.8	88.8	88.8	131.1
3	49.8	49.8	49.8	74.7	61.6	61.6	61.1	91.1
3.5	36.6	36.6	31.7	54.9	45.3	45.3	38.5	66.9
4	28.0	28.0	21.3	42.0	34.7	34.4	25.8	51.2
4.5	22.2	19.9	14.9	33.2	27.4	24.1	18.1	40.5
5	17.9	14.5	10.9	26.9	22.2	17.6	13.2	32.8
6	12.5	8.4	6.3	18.7	15.4	10.2	7.6	22.8

Theoretical allowable loads are based on uniform span lengths. LL (S) is allowable live load based on stress limitation. LL (D) is allowable live load based on deflection limitation of L/180 or L/240. WL is allowable wind load and has been increased by 33.33%.

# PANEL-LOC

Panel-Loc is available in Ultra 26 gauge, Prime 29 gauge, and Standard 29 gauge; in painted or bare Galvalume®. Ultra and Prime panels feature CentralGuard® protection and a lifetime paint warranty. Standard panels feature a 40-year paint warranty.

CentralGuard is our specific combination of everything that goes into making the highest-quality metal panels. Choose CentralGuard for the perfect balance of fade protection, rust blocking, and dent resistance.

Bare (unpainted) Galvalume® and galvanized panels from Central States have an acrylic coating which eliminates using oils during manufacturing and eliminates fingerprinting and foot marking during installation.

The minimum roof slope for 5/8" Panel-Loc is 3:12. If slopes less than 3:12 are needed, International Building Code (IBC) allows a sealant tape to be used on the laps of the panel.

## PANEL CODES


PANEL PROFILE	TYPE	CODE
Panel-Loc™	Ultra SMP	PL6(color)
Panel-Loc™	Prime SMP/FEVE*	PL9(color)
Panel-Loc™	Standard	PL9(color)ST
Panel-Loc™	Thrifty SMP	PL6(color)TH

\*FEVE= Fluorinated Polymer Paint System


# FASTENER SPACING

Follow the suggested fastener patterns below for interior or panel termination. Screws may be placed in either the flat or the rib. In the overlap condition, avoid using fasteners in the major rib as this may damage the siphon groove.

Fastener pattern at panel termination (Eave, endlap, valley, ridge, high eave)



Fastener pattern at interior of panel



# SECTION PROPERTIES - PANEL-LOC

## 36" WIDE, PANEL-LOC™ PANEL

Gauge	Thickness (inches)	Weight (psf)	Yield Stress (ksi)	Top in Compression (Positive Bending)			Bottom in Compression (Negative Bending)		
				Ixx	Sxx	Ma	Ixx	Sxx	Ma
				in <sup>4</sup> /ft	in <sup>3</sup> /ft	in.kips/ft	in <sup>4</sup> /ft	in <sup>3</sup> /ft	in.kips/ft
26 ULTRA	0.0185	0.860	80.0	0.0097	0.0198	0.7097	0.0070	0.0189	0.677
29 PRIME	0.0150	0.698	80.0	0.0073	0.0152	0.5460	0.0053	0.0152	0.5477

Section properties and allowables are calculated in accordance with 1996 AISI Specifications and 1999 AISI Supplement No. 1. I +/- is for deflection determination. S +/- is for bending determination. Ma is allowable bending moment. All values are for one foot of panel width. These loads are for panel strength. Frames, purlins, fasteners and all supports must be designed to resist all loads imposed on the panel. Allowable outward loads based on stress have been increased by 33.33% for wind uplift. Allowable loads for deflection are based on deflection limitation of span/180 or span/240. For roof panels, self weight of the panel has to be deducted from the allowable inward load to arrive at the actual "live load" carrying capacity of the panel. Minimum bearing length must be checked. Minimum deliverable bare steel thickness should not be less than 0.95 of design thickness.

# THEORETICAL ALLOWABLE LIVE & WIND LOADS

## SINGLE SPAN CONDITION

Span (feet)	29 Gauge & 80 ksi				26 Gauge & 80 ksi			
	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)
2	91.0	80.1	60.1	121.4	118.3	105.6	79.2	150.2
2.5	58.2	41.0	30.8	77.7	75.7	54.1	40.6	96.1
3	40.4	23.7	17.8	54.0	52.6	31.3	23.5	66.8
3.5	29.7	15.0	11.2	39.6	38.6	19.7	14.8	49.1
4	22.8	10.0	7.5	30.3	29.6	13.2	9.9	37.6
4.5	18.0	7.0	5.3	24.0	23.4	9.3	7.0	29.7
5	14.6	5.1	3.8	19.4	18.9	6.8	5.1	24.0
6	10.1	3.0	2.2	13.5	13.1	3.9	2.9	16.7

## TWO SPAN CONDITION

Span (feet)	29 Gauge & 80 ksi				26 Gauge & 80 ksi			
	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)
2	91.3	91.3	78.2	121.0	112.9	112.9	103.1	157.3
2.5	58.4	53.4	40.1	77.5	72.3	70.4	52.8	100.7
3	40.6	30.9	23.2	53.8	50.2	40.7	30.6	69.9
3.5	29.8	19.5	14.6	39.5	36.9	25.7	19.2	51.4
4	22.8	13.0	9.8	30.3	28.2	17.2	12.9	39.3
4.5	18.0	9.2	6.9	23.9	22.3	12.1	9.1	31.1
5	14.6	6.7	5.0	19.4	18.1	8.8	6.6	25.2
6	10.1	3.9	2.9	13.4	12.5	5.1	3.8	17.5

## THREE OR MORE SPAN CONDITION

Span (feet)	29 Gauge & 80 ksi				26 Gauge & 80 ksi			
	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)
2	106.6	106.6	106.6	141.1	131.9	131.9	131.9	183.8
2.5	68.2	68.2	58.1	90.5	84.4	84.4	76.5	117.6
3	47.4	44.8	33.6	62.8	58.6	58.6	44.3	81.7
3.5	34.8	28.2	21.2	46.2	43.1	37.2	27.9	60.0
4	26.7	18.9	14.2	35.3	33.0	24.9	18.7	45.9
4.5	21.1	13.3	10.0	27.9	26.1	17.5	13.1	36.3
5	17.1	9.7	7.3	22.6	21.1	12.8	9.6	29.4
6	11.8	5.6	4.2	15.7	14.7	7.4	5.5	20.4

Theoretical allowable loads are based on uniform span lengths. LL (S) is allowable live load based on stress limitation. LL (D) is allowable live load based on deflection limitation of L/180 or L/240. WL is allowable wind load and has been increased by 33.33%.

# DELIVERY

---

Deliveries will be made using a 65' tractor/trailer weighing approximately 80,000 lbs. It is imperative that all delivery locations be accessible by a vehicle of this size. Our drivers have the authority to refuse delivery to any location they see as unsafe or inaccessible. The customer is responsible

for any charges incurred if truck is detained for any reason. The customer is responsible for unloading all trucks. Any damage that occurs at this point is the customer's responsibility. There must be equipment available to unload the truck. Moffett deliveries require at least one person to assist with unloading.

# CARE AND HANDLING

---

## STAGE

Galvalume® steel panels have a good service life when exposed to normal weather conditions; however, to protect the appearance of panels and trims from damage, there are a few simple precautions that can be taken. The steel panels are subject to stain when water sits upon, or becomes trapped between the sheets. If the Galvalume® panels are to be stored for any period of time, they should be stored only in a dry place, preferably under a roof. Stand panels on end and fan them out at the bottom to provide air circulation and moisture run off. If space does not allow this, the panels should be separated, blocked off of the floor at least 12 inches to allow air flow, and stored at an incline to encourage drainage. The panels should then be covered, yet still have good air flow through the sheets to prevent condensation. Do not use a plastic cover, as this may cause the panels to sweat or condensation to occur.

## STORAGE

Failure to follow these steps may result in wet storage stains and premature rusting. The manufacturer's warranty will be void at this time, and the manufacturer will not be responsible.

## HANDLING

When unloading panels, extreme caution must be employed. Care needs to be used when unloading panels with a forklift. Panel edges and underside paint may become damaged if the forklift driver does not use caution. Once at the job site, care must be taken in order to protect the painted surface. When unbundling the panels, never drag them across the surface of one another. This may cause scratches across the underneath panels. It is recommended that the panels be "rolled" off the top of the bundle to prevent scratching. Never lift panels by the ends, instead lift the panels longitudinally and carry vertically.

Panel edges are very sharp, therefore, safety equipment should be worn by all workers handling the material.



Strippable film on Textured panels and trim must be removed within 30 days of manufacture date. Strippable that is left on for more than 30 days may be hard to peel off and is not a reason for a refund or replacement from the manufacturer.



# CARE AND HANDLING

## CUTTING

A portable field shear is the ideal method for cutting panels. Nibblers or a power shear may also be used. Although we do not recommend it, if you decide to cut with a saw, it is very important that the panels be turned upside down during cutting so that hot shavings do not come in contact with the painted surface. Make sure all adjacent panels are covered so that shavings are not imbedded in these panels. If metal shavings become imbedded in the paint surface, they will quickly rust. To avoid this, panels should be thoroughly wiped of all filings on both sides of the panel. Failure to comply with the recommended cutting procedures releases the manufacturer of any responsibility.

Shavings created by saw cutting or drilling may cause the panel to rust and will void warranties in affected areas.




## DRILLING

Panels should not be drilled while stacked. This will cause shavings that will become imbedded in the paint surface.

# SIPHON GROOVE


Panel-Loc Plus and Panel-Loc have two vertical edges, the overlap and the sidelap. The sidelap edge has a specific bend in the last major rib, called a siphon groove. When the overlap edge is installed on top of the sidelap edge, it creates an air gap that prevents water from wicking under the panel. Panels should be installed with the overlap facing away from the prevailing wind.

Do not damage the siphon groove by using a stitch screw on top of the major rib or clog it with butyl tape.



# CONVERTING PITCH TO DEGREE

Use these charts to calculate degrees when designing custom trim.  
Please specify pitch when ordering.



## SINGLE SLOPE PITCHES

Fascia, Eave, Endwall, Tie-In, Gutter

1:12 PITCH	2:12 PITCH	3:12 PITCH	4:12 PITCH	5:12 PITCH	6:12 PITCH	7:12 PITCH	8:12 PITCH	9:12 PITCH	10:12 PITCH	11:12 PITCH	12:12 PITCH
94°	99°	104°	108°	112°	116°	120°	123°	126°	129°	132°	135°
173°	167°	160°	154°	148°	143°	138°	134°	130°	126°	123°	120°
170°	161°	152°	143°	135°	127°	120°	113°	106°	100°	95°	90°

## DOUBLE SLOPE PITCHES



Hip, Valley

## RIDGE CAP

## TRANSITION TRIM

Find the box that intersects your lower and upper roof pitches.

If the intersection lands in the gray area, select a Lower Transition trim.



### LOWER ROOF PITCH (INCHES OF RISE OVER 12" OF RUN)

	1:12 PITCH	2:12 PITCH	3:12 PITCH	4:12 PITCH	5:12 PITCH	6:12 PITCH	7:12 PITCH	8:12 PITCH	9:12 PITCH	10:12 PITCH	11:12 PITCH	12:12 PITCH	13:12 PITCH	14:12 PITCH	15:12 PITCH	16:12 PITCH	17:12 PITCH	18:12 PITCH
1:12 PITCH		175°	171°	166°	162°	158°	155°	151°	148°	145°	142°	140°	137°	135°	133°	132°	130°	128°
2:12 PITCH	175°		175°	171°	167°	163°	159°	156°	153°	150°	147°	144°	142°	140°	138°	136°	135°	133°
3:12 PITCH	171°	175°		176°	171°	167°	164°	160°	157°	154°	152°	149°	147°	145°	143°	141°	139°	138°
4:12 PITCH	166°	171°	176°		176°	172°	168°	165°	162°	159°	156°	153°	151°	149°	147°	145°	144°	142°
5:12 PITCH	162°	167°	171°	176°		176°	172°	169°	166°	163°	160°	158°	155°	153°	151°	149°	148°	146°
6:12 PITCH	158°	163°	167°	172°	176°		176°	173°	170°	167°	164°	162°	159°	157°	155°	153°	152°	150°
7:12 PITCH	155°	159°	164°	168°	172°	176°		177°	173°	170°	168°	165°	163°	161°	159°	157°	155°	154°
8:12 PITCH	151°	156°	160°	165°	169°	173°	177°		177°	174°	171°	169°	166°	164°	162°	161°	159°	157°
9:12 PITCH	148°	153°	157°	162°	166°	170°	173°	177°		177°	174°	172°	170°	167°	166°	164°	162°	161°
10:12 PITCH	145°	150°	154°	159°	163°	167°	170°	174°	177°		177°	175°	173°	170°	168°	167°	165°	163°
11:12 PITCH	142°	147°	152°	156°	160°	164°	168°	171°	174°	177°		178°	175°	173°	171°	169°	168°	166°
12:12 PITCH	140°	144°	149°	153°	158°	162°	165°	169°	172°	175°	178°		178°	176°	174°	172°	170°	169°

# SQUARE CONVERSIONS

For 26 ga. and 29 ga. low rib panels there are 2 formulas; one for panels measured in inches and one for panels measured in feet. While the actual panel width is 38", there will only be 36" of coverage per panel. Squares are figured based on actual width. One square is equal to a panel 31.579 feet long. One square of metal will give you approximately 94.5 square feet of coverage. One square is equal to 14,400 square inches.

## EXAMPLE USING INCHES:

38 (or width in inches) multiplied by length in inches  
multiplied by # of pieces divided by 14,400

Number of panels = 12       $\frac{38" \times 144" \times 12}{14,400}$  equals 4.56 squares of metal  
Panel width = 38"  
Panel length = 144"  
Square inches = 14,400

## EXAMPLE USING FEET:

length in feet multiplied by # of pieces  
divided by 31.579\*

Number of panels = 12       $\frac{12 \times 12}{31.579}$  equals 4.56 squares of metal  
Panel width = 38"  
Panel length = 12'

\*For 26 ga. Thrifty Panel-Loc Plus or Panel-Loc, use 31.373 in place of 31.579.

## COMMON RAFTER LENGTHS (PEAK TO SIDEWALL)

Running Feet	1:12 Pitch	2:12 Pitch	3:12 Pitch	4:12 Pitch	5:12 Pitch	6:12 Pitch
1	1' 0"	1' 1/8"	1' 3/8"	1' 5/8"	1' 1"	1' 1-3/8"
2	2' 1/8"	2' 3/8"	2' 3/4"	2' 1-1/4"	2' 2"	2' 2-7/8"
3	3' 1/8"	3' 1/2"	3' 1-1/8"	3' 2"	3' 3"	3' 4-1/4"
4	4' 1/8"	4' 5/8"	4' 1-1/2"	4' 2-5/8"	4' 4"	4' 5/8"
5	5' 1/4"	5' 7/8"	5' 1-7/8"	5' 3-1/4"	5' 5"	5' 7-1/8"
6	6' 1/4"	6' 1"	6' 2-1/4"	6' 3-7/8"	6' 6"	6' 8-1/2"
7	7' 1/4"	7' 1-1/8"	7' 2-5/8"	7' 4-1/2"	7' 7"	7' 9-7/8"
8	8' 3/8"	8' 1-3/8"	8' 3"	8' 5-1/4"	8' 8"	8' 11-3/8"
9	9' 3/8"	9' 1-1/2"	9' 3-3/8"	9' 5-7/8"	9' 9"	10' 3/4"
10	10' 3/8"	10' 1-5/8"	10' 3-3/4"	10' 6-1/2"	10' 10"	11' 2-1/8"
11	11' 1/2"	11' 1-7/8"	11' 4-1/8"	11' 7-1/8"	11' 11"	12' 3-5/8"
12	12' 1/2"	12' 2"	12' 4-3/8"	12' 7-3/4"	13' 0"	13' 5"
13	13' 1/2"	13' 2-1/8"	13' 4-3/4"	13' 8-1/2"	14' 1"	14' 6-3/8"
14	14' 5/8"	14' 2-3/8"	14' 8-1/8"	14' 9-1/8"	15' 2"	15' 7-7/8"
15	15' 5/8"	15' 2-1/2"	15' 5-1/2"	15' 9-3/4"	16' 3"	16' 9-1/4"
16	16' 5/8"	16' 2-5/8"	16' 5-7/8"	16' 10-3/8"	17' 4"	17' 10-5/8"
17	17' 5/8"	17' 2-7/8"	17' 6-1/4"	17' 11"	18' 5"	19' 1/8"
18	18' 3/4"	18' 3"	18' 6-5/8"	18' 11-5/8"	19' 6"	20' 1-1/2"
19	19' 3/4"	19' 3-1/8"	19' 7"	20' 3/8"	20' 7"	21' 2-7/8"
20	20' 7/8"	20' 3-3/8"	20' 7-3/8"	21' 1"	21' 8"	22' 4-3/8"
21	21' 7/8"	21' 3-1/2"	21' 7-3/4"	22' 1-5/8"	22' 9"	23' 5-3/4"
22	22' 7/8"	22' 3-5/8"	22' 8-1/8"	23' 2-1/4"	23' 10"	24' 7-1/8"
23	23' 1"	23' 3-3/4"	23' 8-1/2"	24' 3"	24' 11"	25' 8-5/8"
24	24' 1"	24' 4"	24' 8-7/8"	25' 3-5/8"	26' 0"	26' 10"
25	25' 1"	25' 4-1/8"	25' 9-1/4"	26' 4-1/4"	27' 1"	27' 11-3/8"
26	26' 1-1/8"	26' 4-1/4"	26' 9-1/2"	27' 5"	28' 2"	29' 3/4"
27	27' 1-1/8"	27' 4-1/2"	27' 9-7/8"	28' 5-5/8"	29' 3"	30' 2-1/4"
28	28' 1-1/8"	28' 4-3/4"	28' 10-1/4"	29' 6-1/4"	30' 4"	31' 3-3/4"
29	29' 1-1/4"	29' 4-7/8"	29' 10-5/8"	30' 6-7/8"	31' 5"	32' 5-1/8"
30	30' 1-1/4"	30' 5"	30' 11"	31' 7-1/2"	32' 6"	33' 6-1/2"
31	31' 1-3/8"	31' 5-1/8"	31' 11-3/8"	32' 8-1/8"	33' 7"	34' 7-7/8"
32	32' 1-3/8"	32' 5-1/4"	32' 11-3/4"	33' 8-3/4"	34' 8"	35' 9-1/4"
33	33' 1-1/2"	33' 5-1/2"	34' 1/8"	34' 9-3/8"	35' 9"	36' 10-3/4"
34	34' 1-1/2"	34' 5-3/4"	35' 1/2"	35' 10"	36' 10"	38' 1/4"
35	35' 1-1/2"	35' 5-7/8"	36' 7/8"	36' 10-5/8"	37' 11"	39' 1-5/8"

# HOW TO ORDER TRIM


## STEP 1:

In CentralLink™, start by entering the Item ID.

Item ID is made of the TRIM CODE, a GAUGE CODE, and a COLOR CODE.

The TRIM CODE can be found with each drawing next to the trim's name.

The GAUGE CODE and COLOR CODES are found below.



**EXAMPLE:** Ridge Cap, 26 gauge, Rustic

**RCP**   **6**   **RR**  
TRIM CODE   GAUGE CODE   COLOR CODE

Enter Item ID  
RCP6RR

Description: 26, Rustic, Ridge Cap

Pieces: 10   Feet: 12   Inches: 2

CentralLink order screen

## STEP 2:

Then type the number of pieces you need along with the length in feet and inches.

## GAUGE CODES

GAUGE	CODE
26	6
29	9

## COLOR CODES

SMP	PANEL GAUGE	TRIM GAUGE	CODE	TEXTURE SMP	PANEL GAUGE	TRIM GAUGE	CODE
Alamo	29/26	29	AW	Basil*	29	26	BA
Black	29/26	29	BK	Cream*	29	26	CE
Brilliant	29/26	29/26	BI	Granite*	29	26	GT
Brown	29/26	29/26	BR	Linen*	29	26	LN
Burgundy	29/26	29/26	BG	Mineral*	29	26	MI
Burnished Slate	29/26	29/26	BS	Onyx*	29	26	OX
Charcoal	29/26	29/26	CH	Roma*	29	26	RM
Colony	29	26	CG	Sienna*	29	26	SI
Copper Metallic	29	29	CM	Suede*	29	26	SE
Crimson	29/26	29/26	CR	Sumatra*	29	26	SU
Desert	29	26	DS				
Forest	29/26	29/26	DG				
Gallery	29/26	29/26	GB				
Galvalume®	29/26	29/26	GL				
Galvanized	29	29	ZN				
Gray	29/26	29/26	GA				
Hawaiian		26	HB				
Hunter	29/26	29/26	GR				
Ivory	29	29	IV				
Light Stone	29/26	29/26	LS				
Ocean	29/26	29	OB				
Pewter	29	29	PG				
Polar		26	PW				
Rustic	29/26	29/26	RR				
Tan	29/26	29/26	TN				
Taupe	29/26	29/26	TA				


\* Longer lead times may apply.  
Galvalume® is a registered trademark of BIEC International, Inc.

# ROOF TRIMS

Unless otherwise noted, trims come in 29 or 26 gauge, and all angles are 90° or 45°. See page 12 for gauge and color codes.


## RIDGE CAP - Specify pitch.

**RIDGE CAP**  
**RCP** - Girth 13.75"




Recommended for 6:12 or less.

**RIDGE CAP**  
**RC2** - Girth 20.75"




Recommended for all pitches.

**RESIDENTIAL RIDGE CAP**  
**RRCP** - Girth 17"




**FORMED RIDGE CAP**  
**PPFRCP** - Panel-Loc Plus, length 3'  
**PLFRCP** - Panel-Loc, length 3'




29 gauge only. Maximum pitch 4:12. Longer lead times may apply.


**PEAK PLATE**  
**PEAKP**



**PEAK PLATE REVERSED**  
**PEAKPREV**




**PEAK BOX**  
**LRPBOXF** - 13"




Standard 4:12.

**HIP CAP**  
**HIP** - Girth 9"




## RAKE, GABLE, EAVE


**RESIDENTIAL RAKE**  
**RRT** - Girth 10.75"




**RAKE & CORNER**  
**COR** - Girth 13"




**MINI RESIDENTIAL RAKE**  
**RRTM** - Girth 8"




**MINI CORNER**  
**MCRN** - Girth 9.5"



**GABLE**  
**GT6** - Girth 16.5"




**RESIDENTIAL EAVE**  
**RET** - Girth 6.5"




Specify pitch.

**RESIDENTIAL DRIP EDGE**  
**RDC** - Girth 9.5"



90° pitch if not specified.


**FASCIA**  
**FT** - Girth 9"




Specify pitch.

## VALLEY

**VALLEY**  
**VT1** - Girth 19.75"



**VALLEY**  
**VT2** - Girth 20.75"




61° open hem

# ROOF TRIMS


Unless otherwise noted, trims come in 29 or 26 gauge, and all angles are 90° or 45°. See page 12 for gauge and color codes.

## TRANSITION TRIMS - Specify pitch.


**GAMBREL TRIM UPPER**  
**GTU** - Girth 10.25"




**GAMBREL TRIM LOWER**  
**GTL** - Girth 10.25"




**GAMBREL TRIM LOWER**  
**GTL2** - Girth 14.5"




**UNIVERSAL SIDEWALL**  
**SF1** - Girth 9.25"



**UNIVERSAL ENDWALL**  
**EF** - Girth 12.5"




**ENDWALL FLASHING**  
**EFF** - Girth 12"




# WALL TRIMS

Unless otherwise noted, trims come in 29 or 26 gauge, and all angles are 90° or 45°. See page 12 for gauge and color codes.


**INSIDE CORNER**  
**IC1** - Girth 13"



**J-TRIM**  
**JT** - Girth 4.8125"



**WINDOW DRIP CAP**  
**WC** - Girth 3.75"




**FLAT SHEET**  
**FS9** - 29 gauge. Girth 43"  
**FS6** - 26 gauge. Girth 41.5625"




10 sheets or fewer will be packaged in a roll.  
Additional pallet charge on orders of 10 or more.


**RAKE & CORNER**  
**COR** - Girth 13"




**MINI CORNER**  
**MCRN** - Girth 9.5"



**SQUARE BASE**  
**SBA** - Girth 5"



**RAT GUARD**  
**RG** - Girth 4.75"  
**RG1** - Girth 5.5625"




# WALL TRIMS

Unless otherwise noted, trims come in 29 or 26 gauge, and all angles are 90° or 45°. See page 12 for gauge and color codes.

## ANGLE

### POST TRIM


- SA312** - Girth 5.5"
- SA512** - Girth 7.5"
- SA7** - Girth 9"
- SA712** - Girth 9.5"



For hem on other leg, refer to Residential Fascia Trim.


### INSIDE ANGLE

- IA112** - Girth 4"
- IA2X2** - Girth 5"
- IA3X3** - Girth 7"



### DOUBLE ANGLE


- DA1** - Girth 3.5"



Use with wainscot.

### WIDE DOUBLE ANGLE


- DA2** - Girth 4.5"



Use with wainscot.

### SINGLE ANGLE


- SA112** - Girth 4"
- SA2X2** - Girth 5"
- SA3X3** - Girth 7"



## FRAMED OPENING TRIMS


### OVERHEAD DOOR JAMB 7 1/8"

- OHDJ7** - Girth 12.5"



### OVERHEAD DOOR JAMB 7 7/8"


- OHDJWD7** - Girth 12"



With drip edge.


### OVERHEAD DOOR JAMB 9 1/4"

- OHDJ9** - Girth 14.25"



### OVERHEAD DOOR JAMB 9 7/8"


- OHDJWD9** - Girth 14"



With drip edge.


### DOOR POST TRIM

- DJ8** - Girth 12.5"




### DOOR POST TRIM

- DJ9** - Girth 13.5"



### DOOR EDGE


- DJ10** - Girth 11.25"



## SLIDING DOOR TRIMS


### TRACK DOOR JAMB

- TDJT** - Girth 14.375"




### SQUARE TRACK COVER NATL

- NTC** - Girth 12.1875"
- NT2** - Girth 9.125"



### ROUND TRACK COVER

- CTC** - Girth 13"
- DC1** - Girth 17.625"




# SOFFIT/FASCIA

Unless otherwise noted, trims come in 29 or 26 gauge, and all angles are 90° or 45°. See page 12 for gauge and color codes.

## BEADED FASCIA

**BFT9(color)102** - Girth 8.25"




29 gauge only. Length 102"

## RESIDENTIAL FASCIA TRIM

**RFT312** - Girth 5.5"


**RFT512** - Girth 7.5"

**RFT712** - Girth 9.25"




## GABLE BASE SOFFIT

**GB1** - Girth 20.25"



## SOFFIT F ADAPTOR


**SFA** - Girth 4.75"



Random color. Use to make F&J Assembly.


## J-TRIM

**JT** - Girth 4.8125"




Use to make F&J Assembly.

## F&J ASSEMBLY - (SFA & JT)




## SOFFIT J-TRIM

**SJT** - Girth 3.625"




## SOFFIT F&J

**SFJ** - Girth 9.375"



## PANEL-LOC PLUS F&J




**PFJ** - Girth 9.125"



## F CHANNEL

**FC12** - Girth 7.5"


**FC38** - Girth 7.375"





# ACCESSORIES

## BUTYL TAPE



PART #	LENGTH	WIDTH	THICKNESS	ROLLS PER BOX
<b>BT3/8</b> <i>Recommended for Panel-Loc Plus.</i>	45'	3/8"	3/32"	40
<b>BTR</b>	40'	7/8"	3/16"	10
<b>BTL</b>	45'	3/4"	3/32"	24

*Install between fastener and exposed edge.  
Rolls per box may vary by location and vendor. Check with your sales person for details.*


## SEALANT



PART #	SIZE	COLOR
<b>GEO(color)</b>	10.3 oz. tube	clear, gray, white
<b>MRS10(color)</b>	10.3 oz. tube	call for colors
<b>MRS10CLEAR</b>	10.3 oz. tube	clear


## TOUCH UP PAINT

**TP(color)** - SMP, 0.6 oz. bottle w/brush.  
**12PURSP** - Purlin paint, 12 oz. spray.



## DOOR SET - With steel jamb.

**3068DR** - 38" x 81 3/16"  
**KNOB**



*Door knobs sold separately.*

# FASTENERS

Fastener color availability may vary by location, contact your sales consultant for details. Order fasteners in increments of 250 pieces.

TYPE	PART #	LENGTH	DIAMETER	HEAD	COLOR	#BAG
METAL/WOOD	<b>1(color)MW</b>	1"	#10	1/4" Hex	all	250
METAL/WOOD	<b>112(color)MW</b>	1 1/2"	#10	1/4" Hex	all	250
METAL/WOOD	<b>2(color)MW</b>	2"	#10	1/4" Hex	all	250
METAL/WOOD STITCH	<b>34(color)ST</b>	3/4"	#12	1/4" Hex	all	250
METAL/METAL	<b>34(color)MM</b>	3/4"	#12	5/16" Hex	all	250
METAL/METAL	<b>114(color)MM</b>	1 1/4"	#12	5/16" Hex	all	250
METAL/METAL	<b>112(color)MM</b>	1 1/2"	#12	5/16" Hex	AW, BI, GL, GR, LS, ZN	250
METAL/METAL	<b>2ZMM</b>	2"	#12	5/16" Hex	galvanized	250
METAL/METAL LAP	<b>78(color)LAP</b>	7/8"	#14	5/16" Hex	all	250
LOW PROFILE WAFER HEAD	<b>1WFAST</b>	1"	#10	#2 Square drive	galvanized	250
POP RIVET	<b>POP(color)</b>		1/8"		ALL	100

# ACCESSORIES

## CLOSURES - Sold separately or by the box. Longer lead times for Panel-Loc closures.



Panel-Loc Plus outside closure shown.



Panel-Loc Plus inside closure shown.



Panel-Loc Plus closure vent shown.

INSIDE CLOSURE - Length 3'. 100 per box.

- PPCLIN** Panel-Loc Plus
- PPCLINGLUE** Panel-Loc Plus - with adhesive
- PLCLIN** Panel-Loc
- PLCLINGLUE** Panel-Loc - with adhesive

OUTSIDE CLOSURE - Length 3'. 100 per box.


- PPCLOUT** Panel-Loc Plus
- PPCLOUTGLUE** Panel-Loc Plus - with adhesive
- PLCLOUT** Panel-Loc
- PLCLOUTGLUE** Panel-Loc - with adhesive

CLOSURE VENT - Length 3'. 25 rolls per box.

- PPCLV** Panel-Loc Plus
- PLCLV** Panel-Loc

Closure is 1 3/8" tall and may require longer screws for installation. Item may vary from sample shown.

**GRAYFLEX**  
**GRAYFLEX-6** - 24-rolls per box.  
For use with hips and valleys.




Length 20'. Width 1". Thickness 1".

**UNIVERSAL POLYFOAM**  
**POLYG** - With glue. 10-rolls per box.




Length 25'. Width 1 1/2". Thickness 1 1/2".

**FLEXOVENT**  
**FLEXOVENT** - (2) 10' rolls per box.




Length 10'. Width 3". Thickness 1 1/2".

**PROFILE RIDGE VENT**  
**PPVENT** - Net free area 23.3sq.in/ft



Length 100'. Width 3". Thickness 1".

## SKYLIGHTS - For best results, use approved sealant (MRS10SKY) and washer (118WASHER). Skylights should be predrilled. Longer lead times for Panel-Loc skylights.




Panel-Loc Plus skylight shown.


- Panel-Loc Plus - Clear Polycarbonate
- PPSKYPCC8** - Length 8'
  - PPSKYPCC10** - Length 10'
  - PPSKYPCC12** - Length 12'

- Panel-Loc Plus - White Polycarbonate
- PPSKYPCW8** - Length 8'
  - PPSKYPCW10** - Length 10'
  - PPSKYPCW12** - Length 12'

- Panel-Loc - Fiberglass 5 oz. sqft weight
- PLSKY12** - Length 12'



- Skylight Ridge Cap - Universal
- RCPC10** - Clear Polycarbonate
  - RCPCW10** - White Polycarbonate
- Length 10'6". Width 25".




- Skylight Sealant - Clear.
- MRS10SKY** 10.3 oz. tube
- Approved for skylight use.



- Skylight Washer - White.
- 118WASHER** - 100 per bag.
- 1/8" outside diameter, 1/4" inside diameter
- Do not overtighten to allow for expansion of material.

## MASTER PIPE FLASHING - Install in a diamond shape and not parallel to the rib.

Square - Max temperature 250°.



- MPF** - Pipe size .25" to 5.75"
- MPF2** - Pipe size .875" to 4"
- MPF4** - Pipe size 2.75" to 7"
- MPF5** - Pipe size 4" to 8.25"
- MPF6** - Pipe size 4.75" to 10"
- MPF7** - Pipe size 5.5" to 11.5"
- MPF8** - Pipe size 6.75" to 13.5"
- MPF9** - Pipe size 9.5" to 20.5"

Silicone - Orange, high temp max 500°.

- 4SMPF** - Pipe size 2.75" to 7"
- 6SMPF** - Pipe size 4.75" to 10"
- 8SMPF** - Pipe size 6.75" to 13.5"
- 10SMPF** - Pipe size 12" to 28.5"

Square with zipper - Max temperature 250°.



- MPF1ZIP** - Pipe size .5" - 4"
- MPF2ZIP** - Pipe size 4" - 9.25"





Right.  
On Time.  
Every Time.®

[centralstatesco.com](http://centralstatesco.com)